## FULL AIR SYSTEM SIZING A.A 2024/25

Buildin Geome	Locatio Building t trical data Total floor are Number of f	уре			hagen, Denmarl	<i>,</i>		
Geome	Building t trical data Total floor are Number of f	уре			hagen, Denmarl	(		
Geome	t <mark>rical data</mark> Total floor are Number of f			0	Copenhagen, Denmark			
Geome	Total floor are Number of t	aa (m^2)		Office Building				
	Number of	va (m^2)						
	Number of	Total floor area (m^2)			1702.9			
		Number of floors		1				
	Window locations		Located on external walls					
	Shading surfaces		-					
	Height (m)		2.7					
	Windows siz	1.8 x 1.5						
Buildin	g Envelope							
	External wall	s [m]	λ [W/(m·K)]	cp [J/kg·K)]	ρ [kg/m^3]	U [W/(m^2·K)]		
	Internal plaster	0.02	0.7	1000	1400	• [( =)]		
	Rock whool	0.16	0.036	1000	90			
-	Semi hollow bricks	0.25	0.4	1000	1000	0.19		
·	External plaster	0.02	0.9	1000	1800			
	•							
	Internal wall	s [m]	λ [W/(m·K)]	cp [J/kg⋅K)]	ρ [kg/m^3]	U [W/(m^2·K)]		
	Internal plaster	0.01	0.7	1000	1400			
	Concrete panel	0.2	0.58	1000	1400	1.58		
	Internal plaster	0.01	0.7	1000	1400			
	Roof	s [m]	λ [W/(m·K)]	cp [J/kg⋅K)]	ρ [kg/m^3]	U [W/(m^2·K)]		
	Built-up roofing	0.01	0.16	1460	1120			
	Fiberboard sheathing	0.01	0.07	1300	400	0.31		
	Insulation board	0.08	0.03	1210	43	0.01		
	Lightweight concrete	0.10	0.53	840	1280			
	Ground contact floor	s [m]	λ [W/(m·K)]	cp [J/kg·K)]	ρ [kg/m^3]	U [W/(m^2·K)]		
-	Porcelain floor	0.015	1.47	1000	1700			
	Cement mortar	0.03	1.4	1000	2000	0.20		
-	Lightened concrete	0.1	0.33	1000	1200	0.20		
	Scree Ueg ground losses	0.2	0.035	1000 1000	1700 30			
	Ued ground losses	0.15	0.035	1000	30			
	Windows Visible trasr		mittance	Solar he	at gain	U [W/(m^2·K)]		
ľ	Single glazing	0.7	7	0.	7	1.2		

In the following picture the floor plan of the office building is presented:



Figure 1: Floor plan of the office building

## Net floor area of the rooms:

- Office 1 = 83.79 m<sup>2</sup>
- Office 2 =  $83.79 \text{ m}^2$
- Office 3 = 83.79 m<sup>2</sup>
- Workspace = 216.09 m<sup>2</sup>

## Open workspace = 840.19 m<sup>2</sup>

Meeting room =  $260.19 \text{ m}^2$ 

Hallway =  $54.69 \text{ m}^2$ 

#### Storage = $17.39 \text{ m}^2$

Bathroom 1 = 31.49 m<sup>2</sup>

Bathroom 2 = 31.49 m<sup>2</sup>





Set point temperature for heating and cooling was assigned to each room.

Figure 2: Occupancy profiles and set point temperature for heating and cooling

### 1. Monthly heating and cooling energy demand

Attending only to the energy demand to be covered by the heating and cooling systems, the energy and instantaneous net power requirements throughout the year are shown below:





Capacity (W)



# 2. Peak load for heating and cooling

Heating peak load of the building = 66 kW

Cooling peak load of the building = 37.24 kW

Space	Peak Load Heating	Peak Load Cooling
Meeting room	10.19	6.91
Office 1	3.71	1.81
Office 2	3.63	1.82
Office 3	3.61	1.76
Open workspace	29.71	16.93
Workspace	8.58	6.43
Bathroom 1	1.62	0.48
Bathroom 2	1.77	0.45
Hallway	2.54	0.85
Storage	1.03	0.27